Printing date 21.02.2007

Reviewed on 21.02.2007

1 Identification of the substance/preparation and of the company/undertaking

- · Product details
- · Trade name: Xenum Belt Conditioner
- · Article number: 18-00000-4394
- · Application of the substance / the preparation Surface active agent
- **Manufacturer/Supplier:** SWF nv Blekersdijk 33A

9000 Gent Belgium T:+32 9 223 22 10 F: +32 9 225 11 16 E: info@xenum.eu W: www.xenum.eu

· Further information obtainable from: Research & Development

2 Composition/information on ingredients

- · Chemical characterization
- **Description:** Active substance with propellant
- · Dangerous components: CAS: 106-97-8 butane F+; R 12 25-50% EINECS: 203-448-7 CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light Xn, Xi, F, N; R 11-38-51/53-65-67 10-25% EINECS: 265-151-9 CAS: 74-98-6 F+; R 12 10-25% propane EINECS: 200-827-9

• Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

· Hazard description:



Xi Irritant

F+ Extremely flammable

N Dangerous for the environment

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

GB

Printing date 21.02.2007

Reviewed on 21.02.2007

Trade name: Xenum Belt Conditioner

(Contd. of page 1)

4 First-aid measures

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

• Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

· For safety reasons unsuitable extinguishing agents: Water with full jet

· Protective equipment: Mount respiratory protective device.

6 Accidental release measures

· Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.

- \cdot Measures for environmental protection:
- Inform respective authorities in case of seepage into water course or sewage system.
- · Measures for cleaning/collecting: Ensure adequate ventilation.

7 Handling and storage

· Handling:

- **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material.
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· Storage:

• **Requirements to be met by storerooms and receptacles:** Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurized containers.

- \cdot Further information about storage conditions:
- Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 3)

GB

Printing date 21.02.2007

Reviewed on 21.02.2007

Trade name: Xenum Belt Conditioner

Melting point/Melting range: Undetermined.

-97°C

 $200.0^{\circ}C$

Product is not selfigniting.

mixtures are possible.

Product is not explosive. However, formation of explosive air/vapour

Boiling point/Boiling range: -44°C

· Flash point:

· Self-igniting:

· Ignition temperature:

· Danger of explosion:

	(Contd. of page 2)		
· Ingredients with limit va	lues that require monitoring at the workplace:		
106-97-8 butane			
WEL Short-term value: 1	810 mg/m³, 750 ppm		
	Long-term value: 1450 mg/m ³ , 600 ppm		
Carc (if more than (0.1% of buta-1.3-diene)		
Additional information: The lists valid during the making were used as basis.			
· Personal protective equip	pment:		
\cdot General protective and h			
Keep away from foodstuff			
Immediately remove all soiled and contaminated clothing			
Wash hands before breaks and at the end of work.			
Do not inhale gases / fume	es / aerosols.		
Avoid contact with the ski	in.		
Avoid contact with the eye	es and skin.		
· Respiratory protection:			
	or low pollution use respiratory filter device. In case of intensive or longer exposure		
use self-contained respiratory protective device.			
Use suitable respiratory protective device in case of insufficient ventilation.			
Filter AX/P2			
· Protection of hands:			
Solvent resistant gloves			
	naterial on consideration of the penetration times, rates of diffusion and the		
· Material of gloves Nitrile	rubber, NBR		
· Penetration time of glove			
	me has to be found out by the manufacturer of the protective gloves and has to be		
observed.			
· Eye protection:			
Tightly sealed	goggles		
• Body protection: Use pro	ptective suit.		
Physical and chemical properties			
· General Information			
Form:	Aerosol		
A 1/1 111.			
	According to product specification		
Colour: Odour:	According to product specification Characteristic		

(Contd. on page 4) GB

Printing date 21.02.2007

Reviewed on 21.02.2007

Trade name: Xenum Belt Conditioner

	(Contd. of page 3)
• Explosion limits: Lower:	0.8 Vol %
Upper:	10.9 Vol %
· Vapour pressure at 20°C:	8300.0 hPa
· Density at 20°C:	0.62100 g/cm ³
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Solvent content: Organic solvents:	85.0 %
· Solids content:	15.0 %

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- \cdot **Dangerous reactions** No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Acute toxicity:
- · Primary irritant effect:
- \cdot on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological information

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- \cdot **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- · Land transport ADR/RID (cross-border)
- $\cdot \mathbf{ADR/RID \ class:} \qquad 2 \quad 5F \text{ Gases.}$
- · Danger code (Kemler): 23

(Contd. on page 5)

GB

Printing date 21.02.2007

Reviewed on 21.02.2007

Trade name: Xenum Belt Conditioner

		(Contd. of page 4)
· UN-Number:	1950	
 Packaging group: 	-	
 Hazard label 	2.1	
· Description of goods:	1950 AEROSOLS	
· Maritime transport II	ADG:	
· IMDG Class:	2.1	
· UN Number:	1950	
· Label	2.1	
 Packaging group: 	-	
· EMS Number:	F-D,S-U	
· Marine pollutant:	No	
· Proper shipping name	: AEROSOLS	
· Air transport ICAO-TI and IATA-DGR:		
· ICAO/IATA Class:	2.1	
· UN/ID Number:	1950	
· Label	2.1	
· Packaging group:	-	
	: AEROSOLS, flammable, n.o.s	

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

\cdot Code letter and hazard designation of product:



Xi Irritant F+ Extremely flammable

N Dangerous for the environment

· Risk phrases:

12 Extremely flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

2 Keep out of the reach of children.

23 Do not breathe aerosol.

24 Avoid contact with skin.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

· **VOC-CH** 85.00 %

· VOC-EU 527.8 g/l

(Contd. of page 5)

GB

Material Safety Data Sheet According to 91/155 EEC (2001/58/EEC)

Printing date 21.02.2007

Reviewed on 21.02.2007

Trade name: Xenum Belt Conditioner

· Danish MAL Code 5-3

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

- 11 Highly flammable.
- 12 Extremely flammable.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: Research & Development

- Contact: Peter Tossyn
- $\cdot \ \textbf{Sources} \ \textbf{st}$