according to Regulation (EU) No. 1907/2006

X-Treme Winter D

Print date : 07.10.2009 Page 1 of 6

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

X-Treme Winter D

Use of the substance/preparation

Fuel additive

Company/undertaking identification

Company name: Xenum N.V.

Street: Steenkaaistraat 17

Place: B-9200 Dendermonde

Telephone: +32 52 22 38 08 Telefax: +32 52 22 51 60

Contact person: Peter Tossyn
e-mail: info@xenum.eu
Emergency telephone: +32 52 22 38 08

2. Hazards identification

Classification

Indications of danger: Harmful, Irritant, Dangerous for the environment

R-phrases:

Irritating to eyes and skin.

Limited evidence of a carcinogenic effect.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Explication of special hazards for human health and environment

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

3. Composition/information on ingredients

Chemical characterization (Mixture)

Preparation on the basis of hydrocarbons, alcohol, maintenance components such as scent extracts

Hazardous components

EC-No.	CAS-No.	Chemical name	Quantity	Classification
265-150-3		Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrotreated heavy	50 - 55 %	Xn R65-66
265-198-5	64742-94-5	Naphtha (mineral oil)	30 - 35 %	Xn, Xi, N R10-36/38-51-53-65
265-184-9		Kerosine (petroleum), hydrodesulfurized, Kerosine - unspecified	5 - 10 %	Kn R65
202-532-0	96-76-4 2	,4-di-tert-butylphenol	1 - 5 %	Xi, N R36/37/38-50-53
202-049-5	91-20-3 r	aphthalene	1 - 5 %	Carc. Cat. 3, Xn, N R40-22-50-53
202-436-9	95-63-6	,2,4-trimethylbenzene	1 - 5 %	Xn, Xi, N R10-20-36/37/38-51-53
203-604-4	108-67-8	1,3,5-trimethylbenzene, mesitylene	< 1 %	Ki, N R10-37-51-53

Full text of each relevant R phrase can be found in heading 16.

4. First aid measures

according to Regulation (EU) No. 1907/2006

X-Treme Winter D

Print date : 07.10.2009 Page 2 of 6

General information

If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Give nothing to eat or drink. Do not induce vomiting.

Advice to doctor

Hazards identification: Lung irritation.

5. Fire-fighting measures

Suitable extinguishing media

Extinguishing powder. Carbon dioxide (CO2). Sand.

Extinguishing media which must not be used for safety reasons

High power water jet.

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

In case of fire and/or explosion do not breathe fumes. Can be released in case of fire: Carbon dioxide (CO2). Carbon monoxide.

Special protective equipment for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Extinguishing materials should be selected according to the surrounding area.

Fire class B: Burning liquid or melting substances.

6. Accidental release measures

Personal precautions

Provide adequate ventilation. Keep away from unprotected people. Keep upwind. Wear personal protection equipment.

Environmental precautions

Spilled product must not leak into the ground. Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

Methods for cleaning up/taking up

Suitable absorbing material: Kieselguhr. Do not rinse down with water.

7. Handling and storage

Handling

Advice on safe handling

Provide for sufficient ventilation and punctiform suction at critical points.

Advice on protection against fire and explosion

In case of open handling, use devices with built-in suction where possible. Product is: Highly flammable.

according to Regulation (EU) No. 1907/2006

X-Treme Winter D

Print date : 07.10.2009 Page 3 of 6

Further information on handling

Avoid contact with skin and eyes.

Take precautionary measures against static discharges.

Storage

Requirements for storage rooms and vessels

Store only in original container.

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Suitable material for floor covering: Solvent-proof.

Storageclass (VCI):

8. Exposure controls/personal protection

Exposure limit values

Exposure limits (EH40)

CAS-No.	Chemical name	ml/m³	mg/m³	F/ml	Category	Origin
64742-48-9 L	64742-48-9 Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrotreated heavy		1000		TWA (8 h)	
					STEL (15 min)	
91-20-3 N	laphthalene	-	-		TWA (8 h)	CHAN
		-	-		STEL (15 min)	CHAN
95-63-6 1	rimethylbenzenes	25	125		TWA (8 h)	WEL
108-67-8		25	125		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
		-	-		STEL (15 min)	WEL

Exposure controls









Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace.

Respiratory protection

Respiratory protection required in case of: Insufficient absorbtion. und prolonged action.

Hand protection

Tested protective gloves are to be worn:

NBR (Nitrile rubber). (0,33 - 0,5 mm)

Butyl rubber. (0,7 mm)

CR (polychloroprenes, Chloroprene rubber). (0,7 - 1,0 mm) penetration time (maximum wearing period): 480 min

Eye protection

Suitable eye protection: Tightly sealed safety glasses.

Skin protection

Protective clothing: Lab apron.

according to Regulation (EU) No. 1907/2006

X-Treme Winter D

Print date: 07.10.2009 Page 4 of 6

9. Physical and chemical properties

General information

Physical state: liquid
Colour: light yellow
Odour: characteristic

Important health, safety and environmental information

Test method

pH-Value: Not applicable.

Changes in the physical state

Melting point: < -45 °C ASTM D 3307 Boiling point: 200 °C DIN 53171 Flash point: 65 °C DIN 51755

Explosive properties

not Explosive.

Indication applies to the solvent.

Lower explosion limits: 0,6 vol. % DIN 51649
Upper explosion limits: 7 vol. % DIN 51649

Oxidizing properties

not oxidizing.

Density (at 20 °C): 0,85 g/cm³ DIN 51757

Partition coefficient: Undetermined.

Flow time: < 30 s (3 mm) 3 DIN EN ISO 2431

Vapour density: Undetermined.

Other information

Auto-ignition temperature

Gas: > 230 ℃

10. Stability and reactivity

Conditions to avoid

In case of warming: Risk of selfignition.

Materials to avoid

Oxidizing agents.

Hazardous decomposition products

Carbon monoxide. nitrogen oxides (NOx).

11. Toxicological information

Acute toxicity

Acute toxicity, oral LD50: > 2000 mg/kg species: Rat. Method: OECD (Naphtha) Acute toxicity, dermal LD50: > 2000 mg/kg species: Rat. OECD 402 (Naphtha) Acute toxicity, inhalant LC50: 33 mg/l (4h) species: Rat. Method: OECD (Naphtha)

Corrosive and irritant effects

After skin contact: irritant. Practical experience.

according to Regulation (EU) No. 1907/2006

X-Treme Winter D

Print date: 07.10.2009 Page 5 of 6

Sensitising effects

no danger of sensitization.

Severe effects after repeated or prolonged exposure

Has de-greasing effect on the skin. Frequently or prolonged contact with skin may cause dermal irritation.

12. Ecological information

Ecotoxicity

Acute fish toxicity LC50: 14 g/m³ (96 h) Oncorhynchus mykiss

Mobility

The insoluble part can be disposed of mechanically in suitable waste water cleaning plants.

Bioaccumulative potential

No indication of bio-accumulation potential.

Other adverse effects

AOX: The product contains no organically bound Halogen.

13. Disposal considerations

Advice on disposal

Carry out a burning of harzardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

140603

WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (except 07 and 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures Classified as hazardous waste.

14. Transport information

Land transport (ADR/RID)

Other applicable information (land transport)

Not a hazardous material with respect to these transportation regulations.

15. Regulatory information

Labelling

Danger symbols:

Xn - Harmful; N - Dangerous for the environment





Xn - Harmful

N - Dangerous for the environment

Hazardous component(s) to be indicated on label

Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrotreated heavy Naphtha (mineral oil)

naphthalene

R phrases

36/38 Irritating to eyes and skin.

40 Limited evidence of a carcinogenic effect.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Revision no.: 1,00 GB - EN Revision date: 07.10.2009

according to Regulation (EU) No. 1907/2006

X-Treme Winter D

Print date: 07.10.2009 Page 6 of 6

65	Harmful: may cause lung damage if swallowed.
S phrases	
23	Do not breathe Vapour .
26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
57	Use appropriate containment to avoid enviromental contamination.
60	This material and its container must be disposed of as hazardous waste.
61	Avoid release to the environment. Refer to special instructions / Safety data sheets.
62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
36/37	Wear suitable protective clothing and gloves.

Special labelling for certain preparations

Operate if possible out of doors or in a well-ventilated place.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

EU regulatory information

1999/13/EC (VOC): ca. 90% (700 - 710 g/L)

Additional information

Sources of the most important data: 2001/118/EG,1999/45/EG, 91/155/EWG, 67/548/EWG, GefStoffV, WRMG, WHG, TRG 300, TRGS 200, TRGS 220, ADR 2007, IMDG-Code

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Water contaminating class (D): 3 - highly water contaminating

16. Other information

10

Full text of R-phrases referred to under sections 2 and 3

Flammable

20	Harmful by inhalation.
22	Harmful if swallowed.
36/37/38	Irritating to eyes, respiratory system and skin.
36/38	Irritating to eyes and skin.
37	Irritating to respiratory system.
40	Limited evidence of a carcinogenic effect.
50	Very toxic to aquatic organisms.
51	Toxic to aquatic organisms.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
53	May cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.

66

Further Information The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Revision no.: 1,00 GB - EN Revision date: 07.10.2009